

CORPORATE OVERVIEW

POWERPLUS GROUP INC., USA, a leading global manufacturer of a comprehensive range of construction equipment, is part of Worldwide Techno-Equipment Group (1973) Pte Ltd. Established since 1973, POWERPLUS GROUP has evolved into a world-renowned organization that offers machinery unparalleled in price, quality and performance.

POWERPLUS machinery is manufactured with enhanced capacities to exceed even the most stringent international standards of quality and safety. With the aim of producing machinery that is able to withstand even the most extreme climatic conditions and rugged terrains, POWERPLUS Research & Development team which has its Headquarters in the United States, has been the backbone behind all its innovative engineering solutions.

Optimizing the best of technology from the United States, Europe and Japan, POWERPLUS machinery is configured to its ideal technical capabilities. A multinational team of engineers analyzes the data collected from our network of distributors worldwide and are on the constant lookout for ways to maximize the life-span of POWERPLUS machinery.

Today the Company's clientele spans over 100 countries across 6 continents.

At the forefront of setting quality standards, every POWERPLUS machine undergoes a technical review after 2 years and is tested rigorously before a new model is churned out of its production facility.

With an emphasis on delivering value and excellent after-sales service to our customers, the POWERPLUS experience outshines and outclasses its competitors in all aspects.

INTRODUCING THE WORLD'S BEST EXCAVATORS

POWERPLUS Excavators can be counted on to deliver unparalleled performance and unmatched versatility. Easy to maintain, efficient engines and powerful hydraulics make POWERPLUS Excavators the most reliable in the industry.

Combining engineering excellence with a dedication to quality, POWERPLUS Excavators are made durable and hardy to meet the challenges of various applications. With a full line of models, there is a POWERPLUS Excavator to fuel your every mining or construction need. POWERPLUS Excavators are known for their exceptional durability, industry leading technology and innovation.

When it comes to cost efficiency, POWERPLUS Excavators make for one of the lowest cost-per-ton options for moving materials in their class, giving you significant savings and better ROI.

KEY COMPONENTS

- KUBOTA engine
- Steel bushing for boom linkage
- Italian technology heat treatment bucket teeth


PP40S-XI

| kg | 3800 | | | | |
|------------------|--|--|--|--|--|
| m ³ | 0.12 | | | | |
| kN | 30.4 | | | | |
| rpm | 12 | | | | |
| 0 | 30 | | | | |
| ENGINE | | | | | |
| lodel | | | | | |
| hp | 25 | | | | |
| rpm | 2200 | | | | |
| Emission | | | | | |
| UNDERCARRIAGE | | | | | |
| km/h | 4.4 / 2.4 | | | | |
| kPa | 32 | | | | |
| Track Rollers | | | | | |
| Carrier Rollers | | | | | |
| HYDRAULIC SYSTEM | | | | | |
| 1ain Pump | | | | | |
| L/min | 88 | | | | |
| MPa | 22.5 | | | | |
| L | 44 | | | | |
| CABIN | | | | | |
| | m³ m³ kN rpm ° hp rpm km/h kPa | | | | |

An ergonomically designed sound proof cabin, enabling wide operational view, comes standard with designer upholstery, adjustable POWERPLUS mechanical suspension driver's seat, streamline dashboard, aircon and radio/mp3 player for extensive operations with well deserved comfort.

STANDARD SPECIFICATIONS

| DIMENSIONS | | | | |
|-------------------------|--|----|-------|--|
| А | Overall Length | mm | 4915 | |
| В | Overall Width | mm | 1720 | |
| С | Overall Height | mm | 2525 | |
| D | Counterweight Ground Clearance | mm | 595 | |
| Е | Minimum Ground Clearance | mm | 295 | |
| F | Track Length | mm | 2154 | |
| G | Track Gauge | mm | 1420 | |
| Н | Track Width | mm | 1720 | |
| Ι | Track Shoe Width | mm | 300 | |
| J | Turntable Width | mm | 1550 | |
| К | Front Turning Radius | mm | 2530 | |
| | Boom Length | mm | 2535 | |
| | Arm Length | mm | 1400 | |
| WORKING RANGE | | | | |
| L | Maximum Digging Height | mm | 4800 | |
| Μ | Maximum Dumping Height | mm | 3406 | |
| Ν | Maximum Digging Depth | mm | 3208 | |
| 0 | Maximum Vertical Digging Depth | mm | 2957 | |
| Ρ | Maximum Digging Reach | mm | 5480 | |
| Q | Maximum Digging Reach At Ground Level | mm | 5359 | |
| SERVICE REFILL CAPACITY | | | | |
| Fuel | | L | 40 | |
| Hydraulic Oil | | L | 44 | |
| Engine Oil | | L | 7 | |
| Final Drive | | L | 2X0.7 | |



www.powerplus.us

International Division

POWERPLUS GROUP PTE. LTD. Powerplus Building 39 Ubi Crescent, Singapore 408587 Tel: (65) 63399333 Fax: (65) 63399933 Email: enquiry@powerplus.us

Research & Development Facility

POWERPLUS GROUP INC., U.S.A. 2130 N. Arrowhead Avenue, San Bernardino, CA 92405, USA Tel: (1) 909 300 3333 Fax: (1) 909 323 3333 Email: hq@powerplus.us Distributed By:

PDWERPLUS is the registered TM of @ POWERPLUS GROUP INC., USA In the United States of America & Worldwide All rights of manufacturer and of this book reserved. Unauthorized duplication is a violation of application law.

Part of: 🥢 WORLDWIDE TECHNO-EQUIPMENT GROUP (1973) PTE. LTD.